SKID STEER&TRENCHER TIRES

X88

X89/ZM789

I-3

C328/C7503

R-4

S9101

SKID STEER&TRENCHER TIRES:

- Volk has developed a high quality range of tires for intensive use on skid steer loaders,boom lifts,back hoe forklifts and trenchers.
- All the tires have a wide tread pattern design that provides for optimal grip and traction in mud,stones and sandy surface conditions.The cross-ply or diagonal heavy ply construction further insures high stability and maximum safety.The compounds are of high quality allowing for maximum tire life and increased cutting&chipping resistance.

FEATURES:

- Volk engineered
- Designed for heavy duty use to provide top performance
- Steel reinforcement,heavy duty sidewalls and rim guard protection
- Premium compounds for maximum tire life and high cutting&chipping resistance
- Reinforced sidewall for improved protection against side impacts
- Excellent ride quality

SKID STEER&TRENCHER TIRES

SIZE	PR	PATTERN NO.	TYPE	T.D(mm)	Std. Rim	Max Load (kg)	Inflation Pressure (kpa)	S.W.(mm)	O.D.(mm)	TIRE(kg)
14-17.5	16	X88	TL	40	10.50	3875	550	349	945	67.8
12-16.5	14	X88/X89	TL	43	9.75	3075	620	315	861	51.0
10-16.5	14	X88/X89	TL	42	8.25	2725	725	270	785	44.5
12-16.5	14	ZM789	TL	37	9.75	3075	620	315	861	47.1
10-16.5	14	ZM789	TL	36	8.25	2725	725	270	785	36.5
27X8.50-15	10	X89	TL	33	7.00	1460	550	221	686	23.7
5.90-15	8	X89	TL	26	5.00	950	620	152	686	15.7
5.70-12	8	X89	TL	20	4.50	850	620	146	574	9.6
27X10.50-15	8	R-4	TL	23	8.50	1405	415	267	686	21.6
27X8.50-15	8	R-4	TL	23	7.00	1310	415	221	686	20.6
23X8.50-12	8	R-4	TL	18	7.00	920	415	221	596	15.5
12-16.5RG	12	R-4	TL	26	9.75	2865	550	321	820	39.4
12-16.5BG	10	R-4	TL	17	9.75	2540	450	321	820	26.6
10-16.5RG	10	R-4	TL	24	8.25	2135	520	274	774	26.5
10-16.5BG	8	R-4	TL	16	8.25	1880	415	274	774	21.7
12.5/80-18	12	I-3	TL	29	9.00	1190	365	312	1004	46.8
26X12D380	8	HF-3	TL	16	10.00	1550	380	309	670	19.5
29X12.5-15	8	C7503	TL	21.5	10.00	1950	320	325	770	24.2
31X15.5-15	8	C7503	TL	19	13.00	1980	310	402	802	29.5
29X12.5-15	8	S9101	TL	13	10.00	1950	320	320	750	24.0